



PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:

Partek Laboratories, Inc.
225 Hollywood Rd., Houma, LA 70360

(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:

ISO/IEC 17025:2017

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (as outlined by the joint ISO-ILAC-IAF Communiqué dated April 2017):

Mechanical Testing
(As detailed in the supplement)

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Tracy Szerszen
President

Perry Johnson Laboratory
Accreditation, Inc. (PJLA)
755 W. Big Beaver, Suite 1325
Troy, Michigan 48084

Initial Accreditation Date:

January 19, 2023

Issue Date:

January 19, 2023

Expiration Date:

March 31, 2025

Accreditation No.:

104554

Certificate No.:

L23-46

The validity of this certificate is maintained through ongoing assessments based on a continuous accreditation cycle. The validity of this certificate should be confirmed through the PJLA website: www.pjlab.com



Certificate of Accreditation: Supplement

Partek Laboratories, Inc.

225 Hollywood Rd., Houma, LA 70360

Contact Name: Mr. Jason Parks Phone: 985-851-5310

Accreditation is granted to the facility to perform the following calibrations:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Mechanical ^F	Metals	Tensile, Elongation & Yield Strength, customer specified methods	ASTM E8	Max Load 300 000 lbf
		Tensile, Elongation & Yield Strength, Customer specified methods	ASTM E8	Max Load 120 000 lbf
		Impact Testing, customer specified methods	ASTM E23	Max 553 ft-lbf
		Hardness Testing, customer specified methods	ASTM E92 ASTM E384	HV 10kgf 100 to 500
		Hardness Testing, customer specified methods	ASTM E110	HB 99 to 484
		Bend Test, Customer specified methods	ASTM E290	Max load 3 000 lbf

1. The presence of a superscript F means that the laboratory performs testing of the indicated parameter at its fixed location. Example: Outside Micrometer^F would mean that the laboratory performs this testing at its fixed location.